

Options

- Automatic alignment on the steered axles
- Drawbar with rubber suspension
- Drawbar with nitrogen suspension
- Hydraulic jack + hand pump
- Hydraulic jack + line
- Truck lighting + rotation light
- Work light
- Side lights
- Rotation light
- Width lights
- LED lights
- Hydr. axle shift
- Hydr. weight transfer to the tractor
- Hydr. top cylinder (nitrogen suspension) with field and road function
- Hydr. shifting of tank on chassis
- Wide angle cardan
- Cardan with shear bolt protection
- 2 oil lines to the rear
- Galvanized chassis 4000/9500L
- Galvanized chassis 9500/10000L, single axle
- Galvanized chassis 10000/16000L, tandem
- Metallized chassis > 16000L
- Provision for side connection
- Side connection 6" + quick lock
- Side connection 8" + quick lock
- Manuel orientable side connection 6"
- Manuel orientable side connection 8"
- Water gauge in accralite Ø125mm
- Level indicator with float ball
- Powered axles
- Turbo filler
- Liquid tank
- Radiator + screw + coolant
- Oil tray + damper (cyclone)
- Oil tray + damper + air filter
- Pneumatic pump switching: Blowing - 0 - Suction
- Hydr. pump switching: Blowing - 0 - Suction
- Precision spreader
- Provision for mixer + stone catcher
- Stone catcher (cyclone) + mixer
- Mixer without stone catcher
- Mixer 8" + stone catcher 1 side"
- Mixer 8" + stone catcher 2 sides"

Vacuüm pumps

Type	lubrication	Rpm	L/min
BP (B=ballast system - M=indirectly driven 540T - D=directly driven 1000T - A=automatic lubrication)			
MEC9000M	drop	600	9030
MEC11000M	drop	600	11137
MEC11000A	automatic	600	11137
MEC11000AB	automatic	600	11137
MEC11000DL	drop	1400	11137
MEC11000DLA	automatic	1400	11137
MEC11000DLAB	automatic	1400	11137
MEC13500DL	drop	1400	13845
MEC13500DLA	automatic	1400	13845
MEC13500DLAB	automatic	1400	13845
BP			
STAR 60M	drop	600	10800
STAR 72M	drop	600	12750
STAR60DLA	automatic	1200	10800
STAR72DLA	automatic	1200	12750
STAR84DLA	automatic	1200	14800
BP water-cooled pumps			
WPT600MFR	drop	540	12000
WPT720MFR	drop	540	14200
WPT720DFR	drop	1000	14200
JUROP air-cooled			
PNR142	automatic	1000	14200
PNR142 HDR	automatic	110 L/MIN	14200
PNR155	automatic	540 / 1000	15200
DL120	low-maintenance	1000	12500
Worm pump			
Böger	price on request		

Options

- Hydr. suction arm 8", bearing-mounted
- Lateral suction arm 8" for chute
Chute without hose
- Encasement of the wheels with diam. > 1.5 m

Lift device

- Provision for lift device
- Industrial lift device + quick hooks
- Fixed lift device + quick hooks
- Compulsory option for all lift devices
 - Manhole at the top instead of at the back Ø600mm + ladder
 - Hydraulic seal (spring) at the top
- Provisions for injector
 - Manifold with 3 functions, electrical, 40L/min
 - Manifold with 4 functions, electrical, 40L/min
 - Manifold with 5 functions, electrical, 40L/min
 - Manifold with 6 functions, electrical, 40L/min
- 8/3 valve, actuated electrically
- Electrical function 80L/min
- RDS Slurry 6" for precise spreading of the slurry
- Horizontal movement hydr. motor + worm gear
- Sequential block 1DA + return tank
- Raising / lowering
- Macerator
- Operating lock
- Provision switchover function
 - Sequential block + switchover function 1DA + free return
 - Sequential block Vredo 1DA + free return
- Pressure relief valve 3" Inox



DEZEURE NV
 IZENBERGESTRAAT 5, B-8630 VEURNE
 P +32 58 28 00 80
 F +32 58 28 00 88
 info@dezeure.be | www.dezeure.be |



SLURRY SPREADERS

www.dezeure.be



Standard equipment

- Hydraulic brakes
- Pit hose 5m
- Mechanical suspension
- Hydraulic valve
- Moisture trap
- Vacuum pump 10000L
- Swiveling hitching eyelet
- 3 gauge glasses
- Tyres 1400x20
- Lighting
- from 10000L bogie steel mudguards with hose rack
- on tridem: air brakes



Technical data

Volume	Vat length	Pump flow rate
SINGLE AXLE		
5750 L	3800mm	8000L/min
6500 L	4000mm	8000L/min
7500 L	4000mm	10000L/min
8500 L	4000mm	10000L/min
9500 L	4000mm	10000L/min
10000 L	4000mm	10000L/min
11000 L	4000mm	10000L/min
12000 L	4000mm	10000L/min
BOGIE		
10000 L	4500mm	10000L/min
11000 L	4500mm	10000L/min
12000 L	1800mm	10000L/min
14000 L	1850mm	10000L/min
16000 L	1900mm	10000L/min
18000 L	1950mm	12000L/min
20000 L	2000mm	12000L/min
TRIDEM		
20000 L	2000mm	12000L/min
22000 L	2050mm	12000L/min
24000 L	2100mm	12000L/min
26000 L	2200mm	12000L/min
28000 L	2200mm	12000L/min



DYNO

Standard equipment

- Galvanized tank
- Galvanized chassis
- Wheels incorporated to the body
- Vacuum pump 12000L BP
- Pit hose 5m/6"
- Hydr. brake + parking brake (manuel brake)
- Axle BPW #150
- Hydraulic valve
- Reinforced chassis for injectors
- Swiveling hitching eyelet
- Lighting
- Tyres 1400x20

Technical data

Volume	Vat length	Pump flow rate	Axles
10500 L	4000mm	12000L	# 110/10
11500 L	4250mm	12000L	# 150/10
12500 L	4250mm	12000L	# 150/10



BRONTO

Standard equipment

- Extra low construction
- Galvanized chassis + tank
- Reinforced chassis for injector
- Incorporated wheels
- Lighting
- Swiveling hitching eyelet
- Hydr. brake + parking brake (manuel brake)
- Hydraulic valve
- Tandem suspension + reinforced bogie
- Steerable axle with hydr. blocking
- Vacuum pump 12000L
- Pit hose 5m/6"
- Tyres 1400x20

Technical data

Volume	Vat length	Pump flow rate	Axles
14000 L	5250mm	12000L	# 100/10
16000 L	5500mm	12000L	# 110/10
17500 L	6000mm	12000L	# 110/10
19000 L	6000mm	12000L	# 110/10
20500 L	6000mm	12000L	# 150/10

